

MEDICI GIANNI S.R.L.



Brocciatura e Stozzatura

BROCCE DP									Modulo	Diam. prep. foro mm		Lung. brocc. mm
SAE	F.R.S.	FIT	16/32	Pitch	Z	9	a.p.	30°	1,5870	diam.	12,75	44
SAE	F.R.S.	FIT	16/32	Pitch	Z	10	a.p.	30°	1,5870	diam.	14,30	38
SAE	F.R.S.	FIT	8/16	Pitch	Z	11	a.p.	30°	3,1750	diam.	32,00	43
SAE	F.R.S.	FIT	16/32	Pitch	Z	11	a.p.	30°	1,5870	diam.	15,90	40
SAE	F.R.S.	FIT	8/16	Pitch	Z	12	a.p.	30°	3,1750	diam.	35,15	50
SAE	F.R.S.	FIT	12/24	Pitch	Z	12	a.p.	30°	2,1160	diam.	22,90	40
SAE	F.R.S.	FIT	8/16	Pitch	Z	13	a.p.	30°	3,1750	diam.	38,20	60
SAE	F.R.S.	FIT	16/32	Pitch	Z	13	a.p.	30°	1,5870	diam.	19,00	50
SAE	F.R.S.	FILLET	10/20	Pitch	Z	14	a.p.	30°	2,5400	diam.	33,00	75
SAE	F.R.S.	FIT	12/24	Pitch	Z	14	a.p.	30°	2,1160	diam.	27,36	50
SAE	F.R.S.	FIT	24/48	Pitch	Z	14	a.p.	30°	1,0580	diam.	13,62	25
SAE	F.R.S.	FIT	8/16	Pitch	Z	15	a.p.	30°	3,1750	diam.	44,55	59
SAE	F.R.S.	FIT	16/32	Pitch	Z	15	a.p.	30°	1,5870	diam.	21,90	70
SAE	F.R.S.	FIT	8/16	Pitch	Z	16	a.p.	30°	3,1750	diam.	47,50	55
SAE	F.R.S.	FIT	12/24	Pitch	Z	16	a.p.	30°	2,1160	diam.	31,85	45
SAE	F.R.S.	FIT	12/24	Pitch	Z	17	a.p.	30°	2,1160	diam.	33,75	60
SAE	F.R.S.	FIT	16/32	Pitch	Z	17	a.p.	30°	1,5870	diam.	25,20	60
SAE	F.R.S.	FIT	16/32	Pitch	Z	18	a.p.	30°	1,5870	diam.	40,00	35
SAE	F.R.S.	FIT	8/16	Pitch	Z	19	a.p.	30°	3,1750	diam.	57,00	120
SAE	F.R.S.	FIT	16/32	Pitch	Z	19	a.p.	30°	1,5870	diam.	28,25	50
SAE	F.R.S.	FIT	12/24	Pitch	Z	20	a.p.	30°	2,1100	diam.	40,00	100
SAE	F.R.S.	FIT	24/48	Pitch	Z	20	a.p.	45°	1,0580	diam.	19,95	30
SAE	F.R.S.	FIT	16/32	Pitch	Z	21	a.p.	30°	1,5890	diam.	31,60	80
SAE	F.R.S.	FIT	24/48	Pitch	Z	21	a.p.	30°	1,0580	diam.	21,40	40
SAE	F.R.S.	FIT	32/64	Pitch	Z	21	a.p.	45°	0,7930	diam.	16,05	32
SAE	F.R.S.	FIT	24/48	Pitch	Z	22	a.p.	45°	1,0583	diam.	22,58	40
SAE	F.R.S.	FIT	16/32	Pitch	Z	23	a.p.	30°	1,5890	diam.	34,75	60
SAE	F.R.S.	FIT	20/40	Pitch	Z	23	a.p.	30°	1,2700	diam.	27,80	50
SAE	F.R.S.	FIT	24/48	Pitch	Z	23	a.p.	30°	1,0583	diam.	23,50	66,5
SAE	F.R.S.	FIT	16/32	Pitch	Z	24	a.p.	30°	1,5890	diam.	36,50	50
SAE	F.R.S.	FIT	32/64	Pitch	Z	24	a.p.	30°	0,7930	diam.	18,08	40
SAE	F.R.S.	FIT	16/32	Pitch	Z	25	a.p.	30°	1,5878	diam.	38,00	51

Medici Gianni Srl

Via G. Lambrakis, 1 - 42122 Reggio Emilia (RE)

Tel. 0522/333348 - 0522/558774 // Fax. 0522393607

MEDICI GIANNI S.R.L.



BROCCE DP									Modulo	Diam. prep. foro mm	Lung. brocc. mm	
SAE	F.R.S.	FIT	24/48	Pitch	Z	25	a.p.	45°	1,0587	diam.	25,50	35
SAE	F.R.S.	FIT	24/48	Pitch	Z	26	a.p.	45°	1,0583	diam.	26,95	50
SAE	F.R.S.	FIT	16/32	Pitch	Z	27	a.p.	30°	1,5890	diam.	41,00	55
SAE	F.R.S.	FIT	32/64	Pitch	Z	28	a.p.	45°	0,7980	diam.	21,28	50
SAE	F.R.S.	FIT	16/32	Pitch	Z	30	a.p.	30°	1,5890	diam.	46,00	70
SAE	F.R.S.	FIT	16/32	Pitch	Z	35	a.p.	30°	1,2875	diam.	53,80	50

CHIEDERE SEMPRE CONFERMA DEL DIAMETRO DI TORNITURA !!

Medici Gianni Srl
 Via G. Lambrakis, 1 - 42122 Reggio Emilia (RE)
 Tel. 0522/333348 - 0522/558774 // Fax. 0522393607